

Features and Benefits

Magneto Optical (MO) technology gives you the reliable and removable data protection you need for your high capacity files and long term storage needs.

Features include:

Faster backup performance

25 ms access time and 8 MB cache and increase backup performance.

Highly reliable

MTBF of 100,000 POH and MIBF of 750,000 cycles.

High compatibility

Supports 9.1GB media and is backward compatible with RW, LIMDOW, CCW and lower capacity media.

Longer shelf life

Archival shelf life for up to 30 years.

Proven technology

WORM Media provides non-erasable, non-alterable records for compliance needs.

Rewriteable

RW Continuous Composite WORM

5.25 inch cartridges

Capacities of 600MB,650MB, 1.2GB, 1.3GB, 2.3GB, 2.6GB, 4.1GB,4.8GB, 5.2GB, 9.1GB

Variable Sector Size

512, 1024, 2048, 4096 bytes per sector

Convenient

5 pack media packaging

Warranty

One year advance replacement



THE CHALLENGE

You need high capacity data protection that is removable and easy to use. And You need that data protection from a company you can trust. You need data protection found in the MaxOptix™ Magneto Optical technology from Breece Hill.

THE SOLUTION

Magneto Optical (MO) media provides a durable, reliable, high capacity storage medium. In fact, it offers the world's safest storage method. Breece Hill's T7 MO drive delivers 9.1 GB of removable, high capacity storage media to keep your data safe for 30 years or more. Its fast 25 ms access time and more data storage capacity and reduced backup windows. The T7 is backward compatible, supporting previous generations of ISO standard media. It can compress rewriteable (RW), manufacturing media (LIMDOW) and write once (CCW) WORM media to 2.3GB cartridges and reads lower capacity media from 600MB to 1.3GB.

In its seventh generation, the T7 delivers exceptional reliability, with a Mean Time Between Failure (MTBF) of up to 100,000 Power-On Hours (POH) and a Mean Insertions Between Failure (MIBF) of more than 750,000 cycles.

The T7 uses an industry-standard SCSI connection, so you just plug it into any network, drag and drop the files you want to store and start saving your data. It's that simple.

OPTICAL DRIVE

Specifications

	Read/Write	Type
Media	Yes	MO, CCW
Capacity	Yes	MO, CCW
9.1GB (14x)	Yes	MO, CCW
5.2GB (8x)	Yes	MO, CCW
4.8GB (8x)	Yes	MO, CCW
4.1GB (8x)	Yes	MO, CCW
2.6GB (4x)	Read only	MO, CCW
2.3GB (4x)	Read only	MO, CCW
1.3GB (2x)	Read only	MO, CCW
1.2GB (2x)	Read only	MO, CCW
650MB (1x)		
600MB (1x)		

Drives

Cache	8 MByte	
Seek Time	25 ms	
Data Rates	Max 3.0 MB/s	
Async. SCSI	Fast 10.0 MB/s	
Sync., SCSI	6.14 MB/s to 3.07 MB/s	(9.1GB media)
Raw Sustained Rate	5.84 MB/s to 2.87 MB/s	(8.6 GB media)
Sustained Rate	5.5 sec	
Spin Up	3.5 sec	
Spin Down		
SCSI Connectors	1-50 Pin Ribbon (Internal Drive)	2-50 Pin High Density (External Drive)

Reliability

MTBF	100,000 POH	
MIBF	> 750,000 cycles	
Power supply (internal version)	+5V +/-5%, 0.9 A (typ.)	+12V +/-5%, 0.85 A (typ.)
Power supply (external version)	AC 100 - 240 V +/-10%	50/60 Hz, 40W (Max.)

Dimensions

	Width	Height	Length
Internal	14.6 cm	4.13 cm	20.3 cm (no bezel)
External	20.1 cm	6.4 cm	25.1 cm
Weight Internal:	1.5 kg	External: 5 kg	

Environmental

Operating Temperature	5 to 40 C°
Operating Humidity	10% to 90%
Storage Temperature	-30 to 60 C°
Max. Wet Bulb Temp.	26 C°
Acoustic	45 db (A) (Max.)

Agency Approvals

FCC, UL, C-UL, and CE

© 2005 by Breece Hill, LLC.

The statements in this publication are not intended to create any warranty, expressed or implied. Breece Hill, LLC reserves the right to change equipment and performance specifications stated herein at anytime without notice. Breece Hill is a registered trademark of Breece Hill, LLC. All products and product names that appear in this material are for identification purposes only and are acknowledged to be trademarks or registered trademarks of their respective holders.

Breece Hill LLC is ISO 9001:2000 certified



For warranty details see www.breecehill.com



For questions about Breece Hill products, contact:

ZSource.com
Tel 805.495.7480

sales@zsource.com
www.zsource.com